

# **Underground Coal Gasification**

**Dr. Julio Friedmann**

**Dr. Elizabeth Burton**

**Dr. Ravi Upadhye**

**Energy & Environment Directorate  
Lawrence Livermore National Laboratory  
Livermore, California**

**Presented at the Potential for Underground Coal Gasification Meeting  
Washington, DC June 5, 2007**

**Acknowledgements as well to Dr. Michael Blinderman, ErgoExergy, Inc., who provided materials**

# Conclusions regarding UCG

---



**Advanced technology to produce syngas**

**Distinct cost and environmental advantages**

**Environmental hazards readily managed**

**Commercial-scale demos possible**

***Best Practices in Underground Coal Gasification:  
Pending DOE-FE Report***

# Underground coal gasification produces syngas with low capital and low operating cost



***Gasification occurs in situ. The technology is well tested >40 years***

## Environmental benefits


- No mining
- Much less pollution (no  $\text{SO}_x$ ,  $\text{NO}_x$ ; less mercury, particulates)
- Low-cost  $\text{H}_2$  production

## Economic benefits


- No gasifier purchase, operation
- No coal purchase or transport
- Low-cost power generation

## Carbon Management

- Lower cost  $\text{CO}_2$  separation
- Good coincidence between UCG and sequestration sites



# There has been a dramatic increase in commercial UCG interest world-wide



**Over 33 US, 66 FSU projects, and 20 other international pilots**



# New projects proceeding rapidly with aims for a variety of different products



## Linc Energy, Australia (Chinchilla)

- First gas, 1999; continuous for 2.5 years
- 35,000 tons brown coal evacuated
- Current plans for CTL plant

## Eskom, S. Africa (Majuba)

- Ignition Jan. 2007; electric power
- Bituminous coal
- Planning 1000 MW IGCC step out this year

## GAIL, India

- Scheduled production, 2009
- Lignite coal, planned electric power


## XinAo, China

- Pilot ignition, Aug. 2007
- Sub-bituminous; planned methanol plant

Other companies planning or operating hydrogen, synthetic natural gas, F-T, and power with CCS



# US UCG projects






# UCG has substantial economic benefits




- No coal mining; no coal purchase or transport; no ash management
- No gasifier or boiler purchase
- UCG syngas tested with off-the-shelf turbines
- Great flexibility in products (power; synthetic NG, liquids),
- Very low cost H<sub>2</sub> production (\$0.60/mcf; \$2-3/MBTU)



UCG Engineering Ltd.


*These aspects have increased interest in developing countries (India, China) with high sulfur & high ash coals.*



# UCG has substantial environmental benefits



- No coal mining; no coal purchase or transport; no ash management
- Smaller surface footprint
- No  $\text{NO}_x$
- 50% volume of particulates. mercury, arsenic, sulfur, tar
- No  $\text{SO}_x$ ; sulfur management straightforward
- Synergies with carbon management



***These aspects have increased interest in developing countries (India, China) with high sulfur & high ash coals.***



# UCG has real engineering and environmental issues



## Engineering issues


- Cannot control all aspects of gasification
- Volume and composition of syngas fluctuate; still difficult to predict
- Must design surface facilities to handle tar, H<sub>2</sub>S

## Environmental issues

- Like long-wall mining, must manage subsidence
- Concerns over groundwater contamination hazard and risks

***These issues can be managed readily by careful site selection and operation***


Component	UCG model predictions (percent)	Field measurements (percent)
Hydrogen	27.2	27.3
Carbon monoxide	13.0	6.4
Carbon dioxide	19.4	27.2
Methane	7.4	6.4
Water	33.0	33.0



# LLNL Focus: Criteria for site selection & planning



- **Geological Assessments**
  - Structural
  - Stratigraphic
  - Hydrologic
- **Contaminant Transport Prediction**
  - Potential contaminant types from coal and rock mineral compositions
  - Contaminant behavior under UCG burn and post-burn conditions



Stratigraphic category	Lateral Isolation	Overlying Unit Character	Relative Risk
1	Low	Sand-prone	High
2	Low	Shale-prone	Moderate
3	High	Shale-prone	Low
4	Moderate	Shale-prone	Moderate
5	Moderate	Sand-prone	High
6	Low	Sand-prone	High

# UCG can and should always proceed in a way to manage and reduce groundwater risks



## Pressure management

- Operate below hydrostatic pressure
- No flow of VOC out of cavity
- Validated at Chinchilla



## Site selection

- Deeper sites (>200m; >500m preferred)
- More characterization of overburden
- Risk characterization

## Regular monitoring

- Water chemistry, pressure
- Passive geophysics (ERT, microseismic)

***Like all subsurface operations, hazards are real but can be readily managed***






# There are synergies between UCG and CBM development and production



- Production elements at roughly same depths
- Detailed characterization of seam (drilling, production information)
- Production dewatering could lead to more process control
- Possibility to use existing wells as both injection and syngas production wells
- Land-use, management, regulatory issues convergent




Courtesy GasTech, Inc.

# Carbon dioxide can be stored in geological targets, usually as a supercritical phase



***Carbon capture & storage (CCS) has emerged as a new field for reducing greenhouse gas emissions, chiefly CO<sub>2</sub>, through geological sequestration.***



## Saline Aquifers

### Depleted Oil & Gas fields

(w/ or w/o EOR and EGR)

### Unmineable Coal Seams

(w/ or w/o ECBM)

**These formations are likely to be found near coal seams chosen for UCG**

***Carbon capture economics and coincidence of storage targets make an attractive carbon management package***

# Possible synergies between UCG and CCS



- Deeper sites = higher pressures

*Lower capture costs*

- Low risk UCG sites are low-risk CCS sites

- Potential to double monitoring arrays


*Reduce operating costs*

- Co-location of sites and facilities for conventional CCS

*Smaller footprint*

- Potential for use of cavity as storage location

*This requires much more S&T*



***Both UCG and CCS are emerging technologies.  
S&T development can help to enable and accelerate both***



# Technology gaps in UCG can be readily addressed through focused R&D initiatives




## Simulation

- Integration of platforms (CFD, hydrologic, chemistry, surface facilities)
- Improved process models for syngas generation & production
- Improved process models for subsidence, env. fate and transport

## Field pilots and demonstrations

- Application of a broad monitoring suite
- Validation of predictions; model improvements
- Economic characterizations with real facilities
- Ultimately, combined UCG + CCS



***This RD&D agenda is fairly simple, and could be readily addressed through collaborative research programs***

# Conclusions regarding UCG

---



**Advanced technology to produce syngas**

**Distinct cost and environmental advantages**

**Environmental hazards readily managed**

**Commercial-scale demos possible**

# Disclaimer and Auspices Statements



*This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or the University of California, and shall not be used for advertising or product endorsement purposes.*

*This work was performed under the auspices of the U.S. Department of Energy by University of California, Lawrence Livermore National Laboratory under Contract W-7405-Eng-48.*



# DOE & LLNL have been active in UCG for over three decades



- Invented the CRIP (controlled retractable injection point) process (1974-1985)
- Conducted a number of field tests (Hoe Creek, Hanna, Centralia)
- Developed cavity growth models (Thorseness and Britten, 1989)
- Developed a CFD-based model of the UCG process and integrated it with Aspen Plus (Wallman 2004)
- Currently expanding the CFD model to include additional phenomenology
- Developed a large suite of tools for environmental assessment
- Developed methodologies for process control monitoring
- Applied carbon management and CO<sub>2</sub> sequestration expertise to UCG (Blinderman & Friedmann, 2006)