



PRE-ACT

- FOR SAFE AND COST-EFFICIENT CO₂ STORAGE

Peder Eliasson, SINTEF

CSLF Technical Group Meeting

Chatou, 5 November 2019

Pre-ACT background

- Response to first **ACT** call 2016
- Wanted to identify and address main storage-related challenges for **accelerated deployment of CCS** in collaboration with industry.
- Focus on crucial **storage challenges: capacity, confidence, and cost**
- Least common denominator: **pressure**




**Pressure control and conformance management for safe and efficient CO₂ storage
- Accelerating CCS Technologies (Acronym: Pre-ACT)**

www.sintef.no/pre-act

Pre-ACT approach

- Answering to industry needs
- Learning from demonstration, pilot, and field lab data
- Deliverables with focus on industry uptake




Pre-ACT approach

- Answering to industry needs
- Learning from demonstration, pilot, and field lab data
- Deliverables with focus on industry uptake




Pre-ACT impact

- Methodologies and recommendations for **cost-efficient monitoring, reliable conformance assessment and decision making** (Pre-ACT Protocols)
- North Sea case studies:
 - Smeaheia (SINTEF, Equinor, ++)
 - P18-4 (TNO, TAQA, ++)
 - Endurance (BGS, Shell, ++)
- Workshops with industry, stakeholders, researchers
- First Svelvik CO₂ Field Lab campaign





WP1: Pre-injection modelling

- WP leader: Jim White (BGS)
- Study optimal injection planning via effective pressure control
- Focus on understanding propagation and control of pressure increases following injection through a program of modelling and laboratory work




Fault heterogeneity

- Study of the effect of uncertain fault characterisation
- Varying sealing properties in assumed fault relay zones has a major impact on pressure propagation





Lothe et al., 2018




✓ High bottom hole pressure simulated in the Smeaheia area using sealing faults

Pressure modelling


- Effect of geological heterogeneities on pressure studied
- Four different production well locations compared
- Various orientation and degree of heterogeneity (A, B, C, D)
- Influence of connectivity on pressure propagation is clear




5000m




5000m




5000m



5000m



Impact of hypersaline discharge




<http://www.archer.ac.uk/about-archer/news-events/events/image-comp/gallery-2018/>

<https://youtu.be/EmQv4qk0kUo>


WP2: Novel monitoring concepts

- WP leader: Conny Schmidt-Hattenberger (GFZ)
- Minimize cost and get sufficient information by using passive-active monitoring strategy
- Novel concepts for quantification of pore pressure and saturation
- Methods applied to Svelvik CO₂ field lab





Passive-active monitoring workflow

- Sparse, semi-continuous monitoring, with complementary detailed measurements
- Potentially all geophysical methods are suitable
- Investigation of different passive seismic data types
 - Ambient noise
 - Teleseismic, regional earthquakes, micro-seismicity



Ambient Noise Seismic Interferometry



- Vp models (low containment case)



Vp at d_0

Ambient Noise Seismic Interferometry


- Vp models (low containment case)





Vp at d_15

Ambient Noise Seismic Interferometry


- Retrieved auto-correlations (fmax=70)



d_{15}



$(d_{15} - d_0) \times 2$




with random noise

Rock physics inversion



- An integrated methodology for **quantitative CO₂ monitoring** using a Bayesian formulation (accounting for uncertainty) has been developed
- Multiple data sets used to quantify e.g. pressure and saturation

adding measurement error



Svelvik CO2 Field Lab

- Unique laboratory for development and testing of technologies for quantitative monitoring of CO₂ storage
- 1 Injection well, 4 observation wells
- Cross-hole seismic and ERT, in-situ pressure measurements, DAS, DTS, DSS
- Pre-ACT data for pressure-saturation discrimination and quantification
 - First brine injection for pressure change alone
 - Then CO₂ injection for combined saturation and pressure change



File Parameters

1st File

2nd File

Plot Parameters

Read Receiver Locations
 Stack Correction
 Remove Offset
MBAS
trace normalisation
Scale Factor

Marker


Enable Confidence Interval
Pick Channel
Distance [m] Velocity [m/s]

Lowpass Filter

1st File Hz
 2nd File

Highpass Filter

1st File Hz
 2nd File



File Parameters

1st File

2nd File

Plot Parameters

Read Receiver Locations
 Stack Correction
 Remove Offset
MBAS
trace normalisation
Scale Factor

Marker


Enable Confidence Interval
Pick Channel
Distance [m] Velocity [m/s]

Lowpass Filter

1st File Hz
 2nd File

Highpass Filter

1st File Hz
 2nd File



File Parameters

1st File

2nd File

Plot Parameters

Read Receiver Locations

Stack Correction

Remove Offset

MBAS
trace normalisation

Scale Factor

Marker

On/Off

Enable Confidence Interval

Pick Channel

Distance [m] Velocity [m/s]

Lowpass Filter


1st File Hz

2nd File

Highpass Filter

1st File Hz

2nd File



File Parameters

1st File: Latest Load List

2nd File: Load

Plot Parameters

Read Receiver Locations

Stack Correction

Remove Offset

MBAS:

Scale Factor:

Marker

On/Off Write to List

Enable Confidence Interval

Pick Channel: Limit [ms]:

Distance [m]: Velocity [m/s]:

Lowpass Filter

1st File Hz


2nd File

Highpass Filter

1st File Hz

2nd File

Navigation:



File Parameters

1st File Latest Load List

2nd File Load

Plot Parameters

Read Receiver Locations

Stack Correction

Remove Offset

MBAS

trace normalisation All

Scale Factor

Marker

On/Off Write to List

Enable Confidence Interval

Pick Channel Limit [ms]

Distance [m] Velocity [m/s]

Lowpass Filter

1st File Hz


2nd File

Highpass Filter

1st File Hz


2nd File

Exit



WP3: Conformance verification


- WP leader: Stefan Carpentier (TNO)
- Construct a *workflow* integrating *multiple data types* and *uncertainties* for assessing *industrial scale* CO₂ storage site *conformance*
- Definition of ‘conformance’, confidence levels
- Optimal workflow and monitoring plan for determining conformance and making decisions



Saturation, pressure, and conformance

- Large scale CO₂ injection generates widespread changes in the subsurface.
- The consequences can be imaged or appraised with active and passive geophysical measurements and downhole monitoring.
- But what controls the size and scale of the subsurface anomalies?
- And what can a point measurement say about the entire storage reservoir?
- How can limited geophysical measurements demonstrate conformance of a storage site?



Conformance: history matching



- CO2 migration can be accurately imaged with geophysical data.
- Flow simulations, based on the best estimates of reservoir parameters, allow prediction to be made.
- But results do not always match!

Case study

- Injected CO₂ must remain within regulatory/safety bounds
 - Quantity of interest: conformance verification at the end of injection period ($t = T$)



- Monitoring alternatives:


- Time-lapse survey during interval $t = [0, T]$
- How to design the configuration of such a survey?
- Which configuration is most useful for conformance verification at $t = T$?

Value of information




Geological uncertainty

- Geological structures influence propagation of CO₂ plume (e.g., heterogeneities in rock properties)
 - Ensemble of model realizations to characterize geological uncertainty
 - Ensemble of model predictions → Probabilistic conformance assessment






History matching

- Incorporate data measured during CO₂ injection to update model realizations
 - Ensemble-based data assimilation methods




History matching


- Incorporate data measured during CO2 injection to update model realizations
- Ensemble-based data assimilation methods



Survey considerations




- Varying time of acquisition




Value-of-information

- Expected gain (in conformance units) and deployment costs (\$) associated with each configuration in the search of the best trade-off
- **Impact on CCS industry:** More cost-effective monitoring surveys through 1) lower survey effort and 2) faster turnaround leads to 3) earlier decision making and 4) more grip on uncertainties





Value-of-information

- **Expected gain** (in conformance units) and **deployment costs** (\$) associated with each configuration in the search of the best **trade-off**
- **Impact on CCS industry:** 80% result for 20% effort (enough for well-informed decisions)




Value-of-information

- **Expected gain** (in conformance units) and **deployment costs** (\$) associated with each configuration in the search of the best **trade-off**
- **Impact on CCS industry:** 80% result for 20% effort (enough for well-informed decisions)




WP4: Decision making

- WP leader: Alv-Arne Grimstad (SINTEF)
- Investigate and describe procedures that should be set in motion if a conformance test has failed
- Enable knowledge-based decision-making
- Explore consequences of possible actions



WP4 Context


- What does a failed conformance test signify?
- Monitoring data indicates that the storage site behaviour cannot with **sufficient certainty** be said to be consistent with predictions
- Predictions of future storage site behaviour should show safe containment (by "definition")
- A failed conformance test therefore means that we are **not sure** that the site develops in a manner that ensures containment of injected CO₂



*Development of shut-in pressure at Snøhvit Tubåen. Predicted exceed of estimated fracture reactivation pressure (390 bar) led to change of injection plan.
From Hermanrud et al, 2013; Figure 6.*



WP5: Workflow demonstration

- WP leader: Ane Lothe (SINTEF)
- Demonstrate value of project results through **application of the methodology developed in WP1–WP4** to storage scenarios at realistic sites
- **Communicate the results to stakeholders:** authorities, regulators, policy and decision makers, politicians, etc.




Workflow demonstration


- **Smeaheia case** (SINTEF, Equinor)
 - Effect of gas Troll production on regional pressure depletion
 - Base injection plans to account for uncertainties
 - Develop a monitoring plan addressing changing baseline
- **P18-4** (TNO, TAQA)
 - Base-line injection plans will be tested and optimised
 - A monitor plan will be designed
- **Endurance** (BGS, Shell)
 - Case study based on pressure linked injection operations
 - Focus on water extraction and boundary limits to control injection and extraction rates
- **Snøhvit** (SINTEF, Total)
 - Extra case being discussed



Lothe et al. (2018)



Arts et al. (2012)



Stakeholder workshops

- 1st meeting in Trondheim, 10 April 2019
 - "First government exploitation permit for CO₂ storage at the Norwegian Continental Shelf"
- 2nd meeting in Brussels, 10 October 2019
 - "Mission: Safe and cost-efficient CO₂ storage for European industry"
- 3rd meeting in "Oslo", 14 November 2019
 - Svelvik official opening
- 4th meeting (TBD, February 2020)



www.sintef.no/projectweb/svelvik-co2-field-lab



Acknowledgements

This work has been produced with support from the SINTEF-coordinated Pre-ACT project (Project No. 271497) funded by RCN (Norway), Gassnova (Norway), BEIS (UK), RVO (Netherlands), and BMWi (Germany) and co-funded by the European Commission under the Horizon 2020 programme, ACT Grant Agreement No 691712. We also acknowledge the industry partners for their contributions: Total, Equinor, Shell, TAQA.



ACT Pre-ACT project (Project No. 271497)



TOTAL

